

Lot Number	Description	Loading Fees	Location (full)
1	Used-Microfluidics Microfluidizer, Model M700. Stock Number 51831024	0	5175 Winnetka Ave N., New Hope, MN 55428
2	Used-DCI Stainless Steel Jacketed Reactor, 200 Gallon. Has top-entering Pharmix agitator, model 4000K. Internal rated 15 PSI @ 280 deg f, jacket rated 40 psi @ 280 deg f. Built 2015. Stock Number 51831019	0	5175 Winnetka Ave N., New Hope, MN 55428
3	Used-Qualicaps Model Liqfil Super 40 capsule filler.rated up to 40000 capsules/hour, with on board feed pump, agitated and jacketed liquid product hopper. Stock Number 72504022	0	5175 Winnetka Ave N., New Hope, MN 55428
4	Used-Tonazzi Colibri Model 1001 automatic single head plastic and metal tube filler. Capable of speeds from 20 to 100 tubes per minute (depending on application). Tube size range: 10mm - 50mm or 3/8" - 2" (Diameter) x 50mm - 250 mm or 2" - 9-3/4" (height). Has a fill range:3ml - 390ml or (0.1 oz to 13 oz) with changeparts. Equipped with automatic tube feeder, with low tube sensor, 12 position carousel, registration eye, diving nozzles with positive shut-off, no tube / no fill, hot air seal station and trim station. A/B SLC 5/04 PLC and interlocked Lexan guarding. Complete with chiller. CE Certified. Elec: 3/60/460V. Stock Number 72504006	0	5175 Winnetka Ave N., New Hope, MN 55428
5	Used- MGS Model PHS Sideserter capable of speeds up to 250 outserts per minute. Has Nordson Problue hot melt glue system. Stock Number 72504018	0	5175 Winnetka Ave N., New Hope, MN 55428
6	OPEN		
7	Used-Fuji Paudal Marumerizer spheronizer, model QJ400TG, stainless steel construction, with 2.0 mm grooved spheronizing plate with plate lift mechanism, jacketed bowl, side discharge with pneumatically operated plug valve, on base, built 2010. Stock Number 51831012	0	5175 Winnetka Ave N., New Hope, MN 55428
8	Used- DT Kalish (IMA) Single Head Chuck Capper, Model Starcap 5123. Machine is capable of speeds up to 90 bottles per minute. Container size range: height) 1-1/2" - 11", diameter up to 4-1/8". Maximum cap size up to 4-1/2", currently set up on 43mm cr diameter cap. Has 12 pocket starwheel container indexing, integrated cap elevator and cap sorter. Handles screw caps, child resistant and plastic pilfer-proof caps. Small footprint machine; last used in pharmaceutical application. Spare parts available upon request. 10 Amp, 1/60/120V. Stock Number 72504028	0	5175 Winnetka Ave N., New Hope, MN 55428
9	Used-Patterson-Kelley 1-Cubic Foot Solids Processor. Jacketed shell rated for 30 psi @ 250 degrees F. 3/60/460V. Stock Number 51831026	0	5175 Winnetka Ave N., New Hope, MN 55428
10	Used-The Bohanan Versifil, a hard gelatin encapsulation machine designed to fill capsules at a rate of 160 to 700 capsules per minute (fill rate depends on tooling used.) Stock Number 72504014	0	5175 Winnetka Ave N., New Hope, MN 55428
11	Used-Countec Model DMS-60S electronic channel tablet counter. Capable of speeds up to 6,000 tablets per minute. Tablet size range: 3mm - 20mm (diameter) x up to 1.7mm (thickness) capsule and softgel sizes: #00 - #5. Stock Number 72504015	0	5175 Winnetka Ave N., New Hope, MN 55428
12	Used-CapPlus Technologies (CPT) Roller Inspection Table, Model Pharmaspec. Features pharmaceutical-grade stainless steel construction and is rated for up to 200,000 pieces per hour (depending on product size). Has variable speed controls for operator and application. Small footprint design. 1/60/110V. Stock Number 72504027	0	5175 Winnetka Ave N., New Hope, MN 55428
13	Used-Manesty Express Press with precompression. Keyed uppers, b tooling 25 station. Stock Number 51831011	0	5175 Winnetka Ave N., New Hope, MN 55428
14	Used-REB, Inc Automatic Inline Piston Filler, Model IVS. Current set up has 6 pistons with 6-diving fill nozzles. Is rated for speeds from 10 to 120 containers per minute (depending on container size and fill volume). Has a fill range from fractional ounces up to 5 liters (with proper change parts). Has integrated touch screen operator HMI. Is of stainless steel construction. 3/60/220V. Stock Number 72504030	0	5175 Winnetka Ave N., New Hope, MN 55428

15	Used- Kalix Model KX100 Plastic Tube Filler. Capable of speeds up to 80-100 tubes per minute. Tube size range: diameter 13.5mm - 50mm; length 60mm - 220mm. Fill volume range (with change parts): 3cc - 350cc. Equipped with automatic tube loader, piston fill with bottom up fill, hot jaw style heated sealer with water quench, chiller and trim station. Now tooled for 50mm diameter, 175mm length tube, 200 ml volume. 208volt 3 phase w/neutral PLC is Direct logix 305. battery check 4-23-22 was ok. Previous PLC was a GE Fanuc. Stock Number 70876001	250	3575 Morreim Dr, Belvidere, IL 61008
16	Used-Crepaco approximately 500 gallon stainless steel jacketed tank. Has counter rotating agitator. Jacket rated to 75 psi/ Serial number B.1556. Mounted on Casters. Stock Number 51831015	0	5175 Winnetka Ave N., New Hope, MN 55428
17	Used-Permasan/Viatec Approximately 44 gallon OVS Kosher Stainless Steel Tank, S/N 76801. Includes SPX Lightnin Agitator Model XDA33, S/N 2939069 (2015).	TBD	147 Industrial Park Rd, Georgia, VT 05454
18	Used-Lee Stainless Steel Tank, Approximately 300 Gallons, Model 300DBT. 316 SS internal rated for 15PSI Internal at 250 Deg F. Vessel designed for vacuum service internal. Mounted on casters. Built 2005. Serial Number 0018-3-1. National Board number 10302. Stock Number 51831022	0	5175 Winnetka Ave N., New Hope, MN 55428
19	Used-Used-Lee Stainless Steel Tank, Approximately 300 Gallons, Model 300DBT. 316 SS internal rated for 15PSI Internal at 250 Deg F. Vessel designed for vacuum service internal. Mounted on casters. Built 2005. Serial Number 0018-3-1. National Board number 10302. Stock Number 51831023	0	5175 Winnetka Ave N., New Hope, MN 55428
21	Used-Wexxar (Belcor) Model Bel 150 top and bottom case sealer. Stock Number 72504017	0	5175 Winnetka Ave N., New Hope, MN 55428
22	Used- Thermo Ramsey Icore AC8000 Checkweigher capable of speeds from 20 to 200 feet per minute, depending on product and application. Weight range up to 7500 grams with accuracies of +/- 1%. Stainless steel construction, has a 9" long belt infeed, 20" long weigh cell with silent chain conveyor, air reject, with CPU controls. Stock Number 72504024	0	5175 Winnetka Ave N., New Hope, MN 55428
23	Used- Accraply Pressure Sensitive Wraparound Labeler, Model 35PW. Machine is rated for speeds up to 3000" per minute (depending on label and container size). Has a label size range of: .75" to 20" in length and .375" to 6" in height. Can handle containers ranging from .75" to 8" in diameter and 1.75" to 12.5" in height. Has touch screen operator panel, bump wheel container indexing, top hold down. 3/60/220V. Stock Number 72504026	0	5175 Winnetka Ave N., New Hope, MN 55428
24	Used-Alpha (All-Fill) Model CW-10 Checkweigher. Capable of speeds up to 300 packages per minute. Can handle package weights up to 10 lbs with dimensions up to 15" (long) X 10" (wide). Is rated with a +/- 400mg accuracy. Suitable for smaller boxes, bottles, cans, cartons. Last running bundled packages. Uses precision strain gage loadcell technology. Has Alpha HMI control panel, used Allen Bradley 1606-XL power supply. Has (2) 1/4" chains and equipped with a reject arm for downstream mounting. CE Certified. 1/60/110V. Stock Number 72504016	0	5175 Winnetka Ave N., New Hope, MN 55428
25	Used-Approximately 42" Diameter Stainless Steel Accumulation Table. Stock Number 72504019	0	5175 Winnetka Ave N., New Hope, MN 55428
26	Used-Garvery 36" Diameter Stainless Steel Accumulation Table. Stock Number 72504020	0	5175 Winnetka Ave N., New Hope, MN 55428
27	Used-Donaldson Dust Collector. Stock Number 51831009	0	5175 Winnetka Ave N., New Hope, MN 55428
28	Used- Donaldson Torit Downflo Oval Dust Collector, Model DFO 3-3, Approximate 570 Square Feet Filtration Area. (3) Filter cartridges approximate 11" diameter x 26" long, (3) valves. Nominal airflow range 300 to 2,400 CFM. Stock Number 51831016	0	5175 Winnetka Ave N., New Hope, MN 55428
29	Used- Donaldson Torit Downflo Oval Dust Collector, Model DFO 3-3, Approximate 570 Square Feet Filtration Area. (3) Filter cartridges approximate 11" diameter x 26" long, (3) valves. Nominal airflow range 300 to 2,400 CFM. Stock Number 51831017	0	5175 Winnetka Ave N., New Hope, MN 55428
30	Used-Domino Model 320i Laser coder. Stock Number 72504005	0	5175 Winnetka Ave N., New Hope, MN 55428

31	Used-Video Jet Model 1510 ink jet coder. ed Video jet Ink Jet Coder with: Capability: Lines of print: 1 - 510 Characters per inch Line speed: up to 914 feet per minute Character height: 0.079 - 0.40 inches (depending on font)Ink: dye based inks Prints:Alpha-numeric Linear bar codes Data matrix codes Print head:Heated Length: 9.47 inches Diameter: 1.63 inches Umbilical: 9.75 feet long x 0.91 inches diameter Controls: 5.7 inch backlit LCD display with PC style keyboard Message storage capability: 100 presets Stainless steel console construction mounted on stainless steel stand. Stock Number 72504007	0	5175 Winnetka Ave N., New Hope, MN 55428
32	Used-Video Jet Model 1510 Ink Jet Coder. ed Video jet Ink Jet Coder with:Capability:Lines of print: 1 - 510 Characters per inch Line speed: up to 914 feet per minute Character height: 0.079 - 0.40 inches (depending on font)Ink: dye based inks Prints:Alpha-numeric Linear bar codes Data matrix codes Print head:Heated Length: 9.47 inches Diameter: 1.63 inches Umbilical: 9.75 feet long x 0.91 inches diameter Controls: 5.7 inch backlit LCD display with PC style keyboard Message storage capability: 100 presets Stainless steel console construction mounted on stainless steel stand. Stock Number 72504012	0	5175 Winnetka Ave N., New Hope, MN 55428
33	Used-Video jet Model 1510 ink jet coder. ed Video jet Ink Jet Coder with:Capability:Lines of print: 1 - 510 Characters per inch Line speed: up to 914 feet per minute Character height: 0.079 - 0.40 inches (depending on font)Ink: dye based inks Prints:Alpha-numeric Linear bar codes Data matrix codes Print head:Heated Length: 9.47 inches Diameter: 1.63 inches Umbilical: 9.75 feet long x 0.91 inches diameter Controls: 5.7 inch backlit LCD display with PC style keyboard Message storage capability: 100 presets Stainless steel console construction mounted on stainless steel stand. Stock Number 72504013	0	5175 Winnetka Ave N., New Hope, MN 55428
34	Unused- Transtore Metalcraft 300 gallon 316L Stainless steel storage bin. Mfg 2018. Stock Number 51831001	0	5175 Winnetka Ave N., New Hope, MN 55428
35	Unused- Transtore Metalcraft 300 gallon 316L Stainless steel storage bin. Mfg 2018. Stock Number 51831002	0	5175 Winnetka Ave N., New Hope, MN 55428
36	Unused- Transtore Metalcraft 300 gallon 316L Stainless steel storage bin. Mfg 2018. Stock Number 51831003	0	5175 Winnetka Ave N., New Hope, MN 55428
37	Unused- Transtore Metalcraft 300 gallon 316L Stainless steel storage bin. Mfg 2018. Stock Number 51831004	0	5175 Winnetka Ave N., New Hope, MN 55428
38	Unused- Transtore Metalcraft 300 gallon 316L Stainless steel storage bin. Mfg 2018. Stock Number 51831005	0	5175 Winnetka Ave N., New Hope, MN 55428
39	Unused- Transtore Metalcraft 300 gallon 316L Stainless steel storage bin. Mfg 2018. Stock Number 51831006	0	5175 Winnetka Ave N., New Hope, MN 55428
40	Unused- Transtore Metalcraft 300 gallon 316L Stainless steel storage bin. Mfg 2018. Stock Number 51831007	0	5175 Winnetka Ave N., New Hope, MN 55428
41	Unused- Transtore Metalcraft 300 gallon 316L Stainless steel storage bin. Mfg 2018. Stock Number 51831008	0	5175 Winnetka Ave N., New Hope, MN 55428
42	Used- Kramer Pharmaceutical Tablet De-Duster, Model 2000-750, S/N 3.187	250	3575 Morreim Dr, Belvidere, IL 61008
43	Used- Douglas Machine Axiom Wraparound Case/Tray Packer. Capable of Speeds up to 50 cases per minute. Has a case size range: 6.19" - 12.38" (width) x 8.00" - 18.56" (length) x 4.5" - 9.25" (height). Has Allen Bradley Controllogix PLC with Allen Bradley Panelview HMI. Nordson Problue hot melt glue system. Last running nutritional products in cans/cannisters.	TBD	147 Industrial Park Rd, Georgia, VT 05454
44	Used- Quadrel RFID Pressure Sensitive Labeler, Model Q60 EAS Proline. Approximate 50 to 60 labels per minute. Equipped with dual heads (redundant head design) set-up for pressure sensitive RFID tag application..Has a 4-1/2" web width with maximum label width of 4-3/8". Currently setup with 2" peeler plate. Variable speed stepper motor label drive capable of dispensing up to 2200" per minute. Up to a 20" OD label roll. Servo driven label heads. 4-1/2" Wide belt conveyor. Has a Keyence vision system with reject, and Allen Bradley Panelview Plus 700 HMI, A/B micrologix 1400 PLC. Serial # 50588-01/02.Last used on plastic tub with an indentation for rfid tag, (that triggered a buzzer). Once the container was labeled with the RFID tag, it was transferred to a downstream labeler that applied a pressure sensitive label over the tag.	250	3575 Morreim Dr, Belvidere, IL 61008

45	Used- Protech Motorized Boot Washer, Model AMSW10. 17" long x 9" wide boot area. 304 Stainless steel construction. 0.2 hp Motor. 1/60/120 Volt. Serial#AMSW-0047-2018, Built 2018. Purchased for installation at infant nutritional powders plant and never installed.	250	3575 Morreim Dr, Belvidere, IL 61008
46	Used- ILC Dover / DoverPac Containment System Powder Drum Filling Station. Stainless steel construction. Last used in nutraceutical operation.	250	3575 Morreim Dr, Belvidere, IL 61008
47	Used- DTM Purefill 2000 Liquid Filling Line with Garvey Feed Table. Pneumatic Scale Model PSC8 pluggger and Pneumatic Scale (Consolidated) Model TG-8-15 rotary chuck capper. Last running 1 oz infant acetaminophen liquid suspension in pharmaceutical packaging operation with 20mm plug and cap. The Purefill 2000 is a 12 head walking beam style filler with mass flow meters. Unit has 11mm diameter stainless steel diving nozzles with positive shut off. Allen Bradley Control Logix 5561 PLC controls, Allen Bradley Panelview plus 700, A/B ultra 3000 and A/B Kinetix 6000. Line is complete with cleated belt cap feeders, cap and plug feeders and accumulation table. 3/60/480 Volt.	250	3575 Morreim Dr, Belvidere, IL 61008
50	Used- Label-Aire 2111M Air Blow Labeler. Capable of speeds up to 1250" of web per minute. Microprocessor controlled and blows the labels on with a blast of air. Applies labels sized from 3/4" wide by 3/4" long to 4" wide by 5.5" long. Label range of 4" x 5-1/2" with accuracy of +/- 1/32". 12" O.D. Rolls maximum on 3" I.D. cores. Up to 20" roll with powered unwind. Unit is on an adjustable stand. 1/60/115 Volt and 80 psi air required.	250	3575 Morreim Dr, Belvidere, IL 61008
51	Used- Label-Aire 2111M Air Blow Labeler. Capable of speeds up to 1250" of web per minute. Microprocessor controlled and blows the labels on with a blast of air. Applies labels sized from 3/4" wide by 3/4" long to 4" wide by 5.5" long. Label range of 4" x 5-1/2" with accuracy of +/- 1/32". 12" O.D. Rolls maximum on 3" I.D. cores. Up to 20" roll with powered unwind. Unit is on an adjustable stand. 1/60/115 Volt and 80 psi air required.	250	3575 Morreim Dr, Belvidere, IL 61008
52	Used- Label-Aire 2111M Air Blow Labeler. Capable of speeds up to 1250" of web per minute. Microprocessor controlled and blows the labels on with a blast of air. Applies labels sized from 3/4" wide by 3/4" long to 4" wide by 5.5" long. Label range of 4" x 5-1/2" with accuracy of +/- 1/32". 12" O.D. Rolls maximum on 3" I.D. cores. Up to 20" roll with powered unwind. Unit is on an adjustable stand. 1/60/115 Volt and 80 psi air required.	250	3575 Morreim Dr, Belvidere, IL 61008
53	Used- Southworth Products Model Roll C PalletPal Roll-On Leveler with Turntable. Platform 44" x 48". Load capacity 2,500 lbs. Lowered height 2", raised height 30". Raise time 30 seconds. Serial # 59359-01/M059359-100-01. 1/60/115 Volt.	250	3575 Morreim Dr, Belvidere, IL 61008
54	Unused- American Process Systems (Eirich Machine) Non Filtered Bag Dump Station, Model NFBD-200, 304 Stainless Steel. Serial# 4402A, Built 1996.	250	3575 Morreim Dr, Belvidere, IL 61008
55	Unused- American Process Systems (Eirich Machine) Non Filtered Bag Dump Station, Model NFBD-200, 304 Stainless Steel. Serial# 4402B, Built 1996.	250	3575 Morreim Dr, Belvidere, IL 61008
57	Unused- American Process Systems (Eirich Machine) Non Filtered Bag Dump Station, Model NFBD-200, 304 Stainless Steel. Serial# 4402D, Built 1996.	250	3575 Morreim Dr, Belvidere, IL 61008
58	Used-New England Machinery Model NEHCL-200AJ Bulk Bottle Unscrambler. Has Model H/E-40 Bulk Bottle Elevator. Last running 20cc and 40cc bottles in an OTC solid dose bottling operation.	250	3575 Morreim Dr, Belvidere, IL 61008
59	Used- PDC Model 75-M2 High Speed Tamper Evident Neck Bander. Capable of speeds up to 300 containers per minute. Band size range: 3/8" - 3" (diameter) x 3/4" - 4" (height). Has worm-screw infeed, vertical perforation, static eliminator, low film sensor, no band detection. Unit was last set up for 8 oz bottles in pharmaceutical packaging operation. 10 amps. 1 ph, 240V. Machine can be retooled and set to size per application. Ask your AEK sales representative for details and send in your container and band samples for pricing.	250	3575 Morreim Dr, Belvidere, IL 61008

60	Used- Gemco Slant Cone Blender, Model 120 Cubic Foot. Stainless Steel. Approximate 30" straight side x 80" diameter. 38" top cone, 54" bottom cone. 18-1/2" Manway no cover, 12" center bottom outlet. Driven by a 20 hp 3/60/230/460 volt, 1770 rpm motor through a gearbox 16:1. Includes a 3 hp motor. Mounted on Carbon Steel stand. Missing small gear, valve and guards.	250	7180 Reed Road, Coal City, IL 60416
61	Used- Elizabeth Hata Tablet Rotary Press, Model HT-AP55-DU. (55) Filling Stations, approximate 1-1/4" diameter x 2-1/2" deep. Driven by 15 hp 3/60/230/460V, 1780 rpm gear motor through reducer, Ratio 1:12.25. Has Mitsubishi A500 Control. Includes portable control cabinet and a skid of misc. parts. Serial# 1/67.	250	3575 Morreim Dr, Belvidere, IL 61008
62	Used- Steris (Amsco) Century Series Single Door Sterilizer, 15 GPM. Chamber size: 34" wide x 52" tall x 66" deep with Prevac. Chamber and Jacket rated 45psi at -20 to 300 degrees F. Driven by a 2hp 3/60/208-240/460v, 3450rpm motor, through a reducer. Has Allen Bradley Logic 53 PLC controls with Allen Bradley Panelview 600 HMI. Never installed in production. Mounted on a carbon steel frame with casters. National Board # 87274. Serial #0803056.	250	3575 Morreim Dr, Belvidere, IL 61008
63	UNUSED- APV Crepaco 20 Gallon Single Wall Stainless Steel Tank. Has 2.5" sprayball with a 270 degree pattern at up to 40 gpm. Tanks are 304 stainless steel with #4 finish with welds stripe bead glass. Tanks have a slope bottom with 2" T.C Connection POD outlet. Has a two piece lift off cover. Has 14" diameter x 32" and 30" straight wall heights. Overall tank height is 44.75" and mounted on three stainless steel legs. Never used in production.	250	7180 Reed Road, Coal City, IL 60416
64	UNUSED- APV Crepaco 20 Gallon Single Wall Stainless Steel Tank. Has 2.5" sprayball with a 270 degree pattern at up to 40 gpm. Tanks are 304 stainless steel with #4 finish with welds stripe bead glass. Tanks have a slope bottom with 2" T.C Connection POD outlet. Has a two piece lift off cover. Has 14" diameter x 32" and 30" straight wall heights. Overall tank height is 44.75" and mounted on three stainless steel legs. Never used in production.	250	7180 Reed Road, Coal City, IL 60416
65	UNUSED- APV Crepaco 20 Gallon Single wall stainless steel tank. Has 2.5" sprayball with a 270 degree pattern at up to 40 gpm. Tanks are 304 stainless steel with #4 finish with welds stripe bead glass. Tanks have a slope bottom with 2" T.C Connection POD outlet. Has a two piece lift off cover. Has 14" diameter x 32" and 30" straight wall heights. Overall tank height is 44.75" and mounted on three stainless steel legs. Never used in production.	250	7180 Reed Road, Coal City, IL 60416
66	UNUSED- APV Crepaco 50 Gallon Single Wall Stainless Steel Tank. Has 2.5" sprayball with a 270 degree pattern at up to 40 gpm. Tanks are 304 stainless steel with #4 finish with welds stripe bead glass. Tanks have a slope bottom with 2" T.C Connection POD outlet. Has a two piece lift off cover. Has 22" diameter x 32" and 30" straight wall heights. Overall tank height is 44.75" and mounted on three stainless steel legs. Never used in production.	250	7180 Reed Road, Coal City, IL 60416
68	Unused- Lightnin Agitator, Model XJ-30. Approximate 5/8" diameter x 24" long stainless steel shaft with 3-blade turbine. Driven by 0.30hp, 3/60/50/208-220/440 volt, 1725/1450 rpm motor. Serial# 95/31929-3...	250	7180 Reed Road, Coal City, IL 60416
69	Used- Alloy Products Pressure Tank, Approximate 30 Gallon, 316L Stainless Steel, Vertical. Approximate 22" diameter x 14" straight side. Internal pressure rated 72 psi at -20 to 100 degrees F. Openings Top (2) 6", (2) 1/4", 1/2" center bottom outlet. Mounted on a cart. Serial # C211571-1-001. Built 2010.	250	3575 Morreim Dr, Belvidere, IL 61008
70	Used- Mueller 2000 Liter Mix Tank, Model D, 528 Gallons, 304 Stainless Steel, Vertical. Approximate 54" diameter x 60" straight side. Dished top, sloped bottom. Top offset entering Lightnin model XJC-65AM, serial# 95/E37815, 3-blade prop driven by 1/2hp, 3/60/230/460 volt, 1730 rpm motor. Jacketed, no tag or pressure rating. Opening top: 6" (agitator), 3" enter, Side: 4", 1-1/2". 1-1/2" Side bottom outlet. Mounted on (4) legs. Serial# P-8741-6.	250	7180 Reed Road, Coal City, IL 60416
71	UNUSED- APV Crepaco 20 Gallon Single Wall Stainless Steel Tank. Has 2.5" sprayball with a 270 degree pattern at up to 40 gpm. Tanks are 304 stainless steel with #4 finish with welds stripe bead glass. Tanks have a slope bottom with 2" T.C Connection POD outlet. Has a two piece lift off color. Has 14" diameter x 32" and 30" straight wall heights. Overall tank height is 44.75" and mounted on three stainless steel legs. Never used in production.	250	7180 Reed Road, Coal City, IL 60416

72	Used- Mueller 1,325 Liter Mix Tank, 304 Stainless Steel, Horizontal. Approximate 350 gallon. Approximate 42" diameter x 70" straight side. Dished ends. Top center entering Lightin model N33G-33AM agitator with (3) blade prop, requires 1/3 hp, 3/60/230/460 volt motor. Openings top: 5" (agitator), 1-1/2", side: 20-1/2" x 15-1/2" manway with cover, 4" sight glass, 1" npt, 1" tri-clamp. 1-1/2" End bottom outlet. Mounted on 4 legs with casters. Serial# P-8741-2.	250	7180 Reed Road, Coal City, IL 60416
73	Used- Mueller 1,325 Liter Mix Tank, 304 Stainless Steel, Horizontal. Approximate 350 gallon. Approximate 42" diameter x 70" straight side. Dished ends. Top center entering Lightin model N33G-33AM agitator with (3) blade prop, requires 1/3 hp, 3/60/230/460 volt motor. Openings top: 5" (agitator), 1-1/2", side: 20-1/2" x 15-1/2" manway with cover, 4" sight glass, 1" npt, 1" tri-clamp. 1-1/2" End bottom outlet. Mounted on 4 legs with casters. Serial# P-8741-3.	250	7180 Reed Road, Coal City, IL 60416
74	UNUSED- APV Model W 30/50 Centrifugal Pump, Stainless Steel. Approximate 280 gallons per minute, 130 head feet @ 3500 rpm. Approximate 3" inlet, 2-1/2" outlet. Approximate 6.3" diameter impellar. Driven by a 20 hp, 3/60/230/460 volt, 3525 rpm motor.	250	7180 Reed Road, Coal City, IL 60416
75	Unused- APV Model W 30/50 Centrifugal Pump, Stainless Steel. Approximate 280 gallons per minute, 130 head feet @ 3500 rpm. Approximate 3" inlet, 2-1/2" outlet. Approximate 6.3" diameter impellar. Driven by a 20 hp, 3/60/230/460 volt, 3525 rpm motor.	250	7180 Reed Road, Coal City, IL 60416
76	Unused- Schlueter Eductor / Pump Hopper, 304 Stainless Steel, Vertical. Approximate 36" diameter x 26" long cone bottom. Vibrator bracket, requires vibrator. Openings top: (2) 6", (2) 2". 4" Center bottom outlet. Mounted on (4) legs.	250	3575 Morreim Dr, Belvidere, IL 61008
77	Unused- Schlueter Eductor / Pump Hopper, 304 Stainless Steel, Vertical. Approximate 36" diameter x 26" long cone bottom. Vibrator bracket, requires vibrator. Openings top: (2) 6", (2) 2". 4" Center bottom outlet. Mounted on (4) legs.	250	3575 Morreim Dr, Belvidere, IL 61008
78	Unused- Schlueter Eductor / Pump Hopper, 304 Stainless Steel, Vertical. Approximate 36" diameter x 26" long cone bottom. Vibrator bracket, requires vibrator. Openings top: (2) 6", (2) 2". 4" Center bottom outlet. Mounted on (4) legs.	250	3575 Morreim Dr, Belvidere, IL 61008
79	Unused- Ultra Industries Dust Collector, Model BB25. Approximately 40" long x 40" wide x 38" tall chamber, 31-1/2" coned bottom. (25) Bag filters. 8" diameter side top & bottom openings. 8" x 8" center bottom outlet. Mounted on (4) legs. Serial# BB 3712.	250	3575 Morreim Dr, Belvidere, IL 61008
80	Unused- Ultra Industries Dust Collector, Model BB25. Approximately 40" long x 40" wide x 38" tall chamber, 31-1/2" coned bottom. (25) Bag filters. 8" diameter side top & bottom openings. 8" x 8" center bottom outlet. Mounted on (4) legs. Serial# BB 3713.	250	3575 Morreim Dr, Belvidere, IL 61008
81	Unused- FEC Food Engineering Corp X-Force Horizontal Motion Conveyor, 304 Stainless Steel. Approximately 21" wide x 12' long pan. Driven by a 1hp, 3/60/230/460 volt, 1200 rpm drive motor. Equip# CY-11003, Built 1995.	250	3575 Morreim Dr, Belvidere, IL 61008
82	Unused- FEC Food Engineering Corp X-Force Horizontal Motion Conveyor, 304 Stainless Steel. Approximately 21" wide x 12' long pan. Driven by a 1hp, 3/60/230/460 volt, 1200 rpm drive motor. Equip# CY-12003, Built 1995.	250	3575 Morreim Dr, Belvidere, IL 61008
83	Unused- Schlueter Insulated 1,200 Gallon Tank, Stainless Steel, Vertical. Approximate 64" diameter x 87" straight side. Flat top and bottom. Openings top: 18" manway with cover, (6) 2", side: (2) 2", (2) 3" side bottom outlets, bottom: 4" (vent tube), 2". Side ladder. Mounted on (4) legs. No mfg tag. Brand new, still in crate.	250	7180 Reed Road, Coal City, IL 60416
84	Used- Stainless Steel Tank, Approximate 135 Gallon, 304 Stainless Steel, Vertical. Approximate 33" diameter x 37" straight side. Dished top, sloped bottom. Openings: 16" manway with cover, (2) 3", 1", side: 4", 1-1/2". 2" Side bottom outlet. Spray ball. Mounted on (4) legs. No mfg tag.	250	7180 Reed Road, Coal City, IL 60416
85	Used- Stainless Steel Tank, Approximate 135 Gallon, 304 Stainless Steel, Vertical. Approximate 33" diameter x 37" straight side. Dished top, sloped bottom. Openings: 16" manway with cover, (2) 3", 1", side: 4", 1-1/2". 2" Side bottom outlet. Spray ball. Mounted on (4) legs. No mfg tag.	250	7180 Reed Road, Coal City, IL 60416

86	Used- Walker 135 Gallon Stainless Steel Tank, Model SB-V-52, 304 Stainless Steel, Vertical. Approximate 36" diameter x 30" straight side. Dished top, sloped bottom. Openings: 16" manway with cover, 4", (2) 2", 1", side: 4", 1-1/2", 1". 2" Side bottom outlet. Spray ball. Mounted on (3) legs. Serial# 2522, Built 1983.	250	7180 Reed Road, Coal City, IL 60416
87	Used- Walker 135 Gallon Stainless Steel Tank, Model SB-V-52, 304 Stainless Steel, Vertical. Approximate 36" diameter x 30" straight side. Dished top, sloped bottom. Openings: 16" manway with cover, 4", (2) 2", 1", side: 4", 1-1/2", 1". 2" Side bottom outlet. Spray ball. Mounted on (3) legs. Serial# 2523, Built 1983.	250	7180 Reed Road, Coal City, IL 60416
88	Used-Hoover Industrial Tote Bin, 304 Stainless Steel. Approximate 48" x 42" x 10" straight side x 28" long cone. Flat top, cone bottom. Openings top: 23" manway with cover, side: 6" x 3" sight glass. 6" Center bottom outlet with manual butterfly valve. Mounted on frame with casters.	250	7180 Reed Road, Coal City, IL 60416
89	Used-Hoover Industrial Tote Bin, 304 Stainless Steel. Approximate 48" x 42" x 10" straight side x 28" long cone. Flat top, cone bottom. Openings top: 23" manway with cover, side: 6" x 3" sight glass. 6" Center bottom outlet with manual butterfly valve. Mounted on frame with casters.	250	7180 Reed Road, Coal City, IL 60416
90	Used-Hoover Industrial Tote Bin, 304 Stainless Steel. Approximate 48" x 42" x 10" straight side x 28" long cone. Flat top, cone bottom. Openings top: 23" manway with cover, side: 6" x 3" sight glass. 6" Center bottom outlet, no valve. Mounted on frame with casters.	250	7180 Reed Road, Coal City, IL 60416
91	Used-Hoover Industrial Tote Bin, 304 Stainless Steel. Approximate 48" x 42" x 10" straight side x 28" long cone. Flat top, cone bottom. Openings top: 23" manway with cover, side: 6" x 3" sight glass. 6" Center bottom outlet, no valve. Mounted on frame with casters.	250	7180 Reed Road, Coal City, IL 60416
92	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W150/50. Approximate 346 gallons per minute, 236 head feet @ 3500 rpm. Approximate 3" inlet, 2" outlet. Driven by a 15hp, 3/60/230/460 volt, 3525 rpm motor. Serial# H-9340-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
93	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W40/20. Approximate 120 gallons per minute, 190 head feet @ 3500 rpm. Approximate 2" inlet, 1.5" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9341-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
94	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9328-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
95	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9310-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
96	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9311-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
97	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9312-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
98	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9303-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
99	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9306-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
100	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9291-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
101	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9296-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416





119	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 3/4hp, 3/60/230/460 volt, 3450 rpm motor. Serial# H-9331-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
120	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 3/4hp, 3/60/230/460 volt, 3450 rpm motor. Serial# H-9332-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
121	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 3hp, 3/60/208-230/460 volt, 3450 rpm motor. Serial# H-9343-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
122	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 2hp, 3/60/208-230/460 volt, 3450 rpm motor. Serial# H-9345-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
123	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W40/20. Approximate 120 gallons per minute, 190 head feet @ 3500 rpm. Approximate 2" inlet, 1.5" outlet. Driven by a 7.5hp, 3/60/230/460 volt, 3520 rpm motor. Serial# H-9342-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
124	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W130/100. Approximate 650 gallons per minute, 141 head feet @ 3500 rpm. Approximate 4" inlet, 3" outlet. Driven by a 25hp, 3/60/230/460 volt, 3535 rpm motor. Serial# H-9322-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
125	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9313-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
126	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9308-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
127	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9294, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
128	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 3hp, 3/60/230/460 volt, 3520 rpm motor. Serial# H-9314, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
129	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 3hp, 3/60/230/460 volt, 3520 rpm motor. Serial# H-9315, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
130	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 3hp, 3/60/230/460 volt, 3520 rpm motor. Serial# H-9316, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
131	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W30/25. Approximate 155 gallons per minute, 141 head feet @ 3500 rpm. Approximate 2.5" inlet, 2" outlet. Driven by a 7.5hp, 3/60/230/460 volt, 3520 rpm motor. Serial# H-9344-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
132	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 3/4hp, 3/60/230/460 volt, 3450 rpm motor. Serial# H-9333-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
133	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 3/4hp, 3/60/230/460 volt, 3450 rpm motor. Serial# H-9335-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
134	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 5hp, 3/60/230/460 volt, 3500 rpm motor. Serial# H-9301-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416

135	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 3/4hp, 3/60/230/460 volt, 3450 rpm motor. Serial# H-9336-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
136	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W20/20. Approximate 105 gallons per minute, 95 head feet @ 3500 rpm. Approximate 2" inlet, 2" outlet. Driven by a 3/4hp, 3/60/230/460 volt, 3450 rpm motor. Serial# H-9337-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
137	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W50/50. Approximate 346 gallons per minute, 236 head feet @ 3500 rpm. Approximate 3" inlet, 2" outlet. Driven by a 15hp, 3/60/230/460 volt, 3525 rpm motor. Serial# H-9339-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
138	Unused- APV Crepaco Centrifugal Pump, Stainless Steel, Model W130/100. Approximate 650 gallons per minute, 141 head feet @ 3500 rpm. Approximate 4" inlet, 3" outlet. Driven by a 25hp, 3/60/230/460 volt, 3535 rpm motor. Serial# H-9325-95, Built 1995.	250	7180 Reed Road, Coal City, IL 60416
139	Unused- Lightnin Agitator, Model XJ-30. Approximate 5/8" diameter x 24" long stainless steel shaft with 3-blade turbine. Driven by 0.30hp, 3/60/50/208-220/440 volt, 1725/1450 rpm motor. Serial# 95/31929-2.	250	7180 Reed Road, Coal City, IL 60416
140	Unused- Lightnin Agitator, Model Xd-30. Approximate 1/2" diameter x 32" long stainless steel shaft, no blade. Driven by 0.30hp, 3/60/50/208-220/440 volt, 1725/1450 rpm motor. Serial# 95/31930-03.	250	7180 Reed Road, Coal City, IL 60416
141	Unused- Lightnin Agitator, Model Xd-30. Approximate 1/2" diameter x 32" long stainless steel shaft, no blade. Driven by 0.30hp, 3/60/50/208-220/440 volt, 1725/1450 rpm motor. Serial# 95/31930-02.	250	7180 Reed Road, Coal City, IL 60416
142	Unused- Lightnin Agitator, Model Xd-30. Approximate 1/2" diameter x 32" long stainless steel shaft, no blade. Driven by 0.30hp, 3/60/50/208-220/440 volt, 1725/1450 rpm motor. Serial# 95/31930-01.	250	7180 Reed Road, Coal City, IL 60416
143	Unused- Lightnin Agitator, Model Xd-30. Approximate 1/2" diameter x 32" long stainless steel shaft, no blade. Driven by 0.30hp, 3/60/50/208-220/440 volt, 1725/1450 rpm motor. Serial# 95/31930-04.	250	7180 Reed Road, Coal City, IL 60416
144	Used- Sullair Reciprocating Compressor with model 16-75, Has 75HP motor. Has 60,531 hours on it. Maximum pressure rating 110 PSIG.	0	147 Industrial Park Rd, Georgia, VT 05454
145	Unused- Sullair Reciprocating Compressor, Model LS-16. Approximately 370 acfm capacity at 100psi. Driven by a 75hp motor. Includes Air Dryer, Model SRD400.	0	147 Industrial Park Rd, Georgia, VT 05454
146	Unused in Box. Sullair Regenerative Air Dryer Product Series Desiccant Modular Dryer, Model DMD-40, Sullair Part Number 02250244-035. Vessel Diameter 5", Vessel Height 40", Vessel Thickness 1/3". Purge Exhaust Muffler 3/4". Inlet-Outlet Connection - Inches 1 1/2" NPT; Relief Valve Setting (psi) 200; Bed Velocity (fpm) 60; Sound Max dbA 85; Purge Source Dry Air; Purge Adjust CHECK VALVE; NEMA Cycle (Min) 5 min; Drying time (Min) 2.5 minutes; Regeneration Time (Min) 2 minutes; Repressurization Time (Min) 30 seconds; PERFORMANCE DATA: MAX Ambient Temp (Deg. F/ Deg. C) 122/50; MIN Ambient Temp (Deg. F/ Deg. C) 34 / 1.6 ; MAX Inlet Temp (Deg. F/ Deg. C) 122/50; Max Rated Air Flow at 100 Deg. F (38 Deg. C) ; Inlet, 100 psig (7 barg) and 100 Deg. F (38 Deg. C) Amb 40; Dryer Delta P 2; MIN Pressure (psi/bar) 58 / 4.0; MAX Pressure (psi/bar) 200 / 16; AVG Purge Rate (at -40 Deg. F) 15%; AVG Purge Rate (at -100 Deg. F) 20%; ELECTRICAL DATA: Standard Voltage 80-240V/ 50-60Hz; Full Load Amps 1; MIN. Circuit Ampacity 2; Input Power kW 0.075; Unit Average kW 0.06; DIMENSIONS & WEIGHT DATA: Single Vessel Desiccant-Lbs 20.9; Ship Weight 164.5; Length-inches 16.1; Width-inches 17.7; Height-inches 49.2; UNIT Weight-lbs 143; Total Desiccant (lbs) 41.8. Serial# 4318MD00606	250	3575 Morreim Dr, Belvidere, IL 61008

147	<p>Unused in Box. Sullair Regenerative Air Dryer Product Series Desiccant Modular Dryer, Model DMD-40, Sullair Part Number 02250244-035. Vessel Diameter 5", Vessel Height 40", Vessel Thickness 1/3". Purge Exhaust Muffler 3/4". Inlet-Outlet Connection - Inches 1 1/2" NPT; Relief Valve Setting (psi) 200; Bed Velocity (fpm) 60; Sound Max dbA 85; Purge Source Dry Air; Purge Adjust CHECK VALVE; NEMA Cycle (Min) 5 min; Drying time (Min) 2.5 minutes; Regeneration Time (Min) 2 minutes; Repressurization Time (Min) 30 seconds; PERFORMANCE DATA: MAX Ambient Temp (Deg. F/ Deg. C) 122/50; MIN Ambient Temp (Deg. F/ Deg. C) 34 / 1.6 ; MAX Inlet Temp (Deg. F/ Deg. C) 122/50; Max Rated Air Flow at 100 Deg. F (38 Deg. C) ; Inlet, 100 psig (7 barg) and 100 Deg. F (38 Deg. C) Amb 40; Dryer Delta P 2; MIN Pressure (psi/bar) 58 / 4.0; MAX Pressure (psi/bar) 200 / 16; AVG Purge Rate (at -40 Deg. F) 15%; AVG Purge Rate (at -100 Deg. F) 20%; ELECTRICAL DATA: Standard Voltage 80-240V/ 50-60Hz; Full Load Amps 1; MIN. Circuit Ampacity 2; Input Power kW 0.075; Unit Average kW 0.06; DIMENSIONS &amp; WEIGHT DATA: Single Vessel Desiccant-Lbs 20.9; Ship Weight 164.5; Length-inches 16.1; Width-inches 17.7; Height-inches 49.2; UNIT Weight-lbs 143; Total Desiccant (lbs) 41.8.</p> <p>Serial# 4318MD00600</p>	250	3575 Morreim Dr, Belvidere, IL 61008
148	<p>Unused in Box. Sullair Regenerative Air Dryer Product Series Desiccant Modular Dryer, Model DMD-40, Sullair Part Number 02250244-035. Vessel Diameter 5", Vessel Height 40", Vessel Thickness 1/3". Purge Exhaust Muffler 3/4". Inlet-Outlet Connection - Inches 1 1/2" NPT; Relief Valve Setting (psi) 200; Bed Velocity (fpm) 60; Sound Max dbA 85; Purge Source Dry Air; Purge Adjust CHECK VALVE; NEMA Cycle (Min) 5 min; Drying time (Min) 2.5 minutes; Regeneration Time (Min) 2 minutes; Repressurization Time (Min) 30 seconds; PERFORMANCE DATA: MAX Ambient Temp (Deg. F/ Deg. C) 122/50; MIN Ambient Temp (Deg. F/ Deg. C) 34 / 1.6 ; MAX Inlet Temp (Deg. F/ Deg. C) 122/50; Max Rated Air Flow at 100 Deg. F (38 Deg. C) ; Inlet, 100 psig (7 barg) and 100 Deg. F (38 Deg. C) Amb 40; Dryer Delta P 2; MIN Pressure (psi/bar) 58 / 4.0; MAX Pressure (psi/bar) 200 / 16; AVG Purge Rate (at -40 Deg. F) 15%; AVG Purge Rate (at -100 Deg. F) 20%; ELECTRICAL DATA: Standard Voltage 80-240V/ 50-60Hz; Full Load Amps 1; MIN. Circuit Ampacity 2; Input Power kW 0.075; Unit Average kW 0.06; DIMENSIONS &amp; WEIGHT DATA: Single Vessel Desiccant-Lbs 20.9; Ship Weight 164.5; Length-inches 16.1; Width-inches 17.7; Height-inches 49.2; UNIT Weight-lbs 143; Total Desiccant (lbs) 41.8.</p> <p>Serial# 4318MD00598</p>	250	3575 Morreim Dr, Belvidere, IL 61008
149	<p>Unused in Box. Sullair Regenerative Air Dryer Product Series Desiccant Modular Dryer, Model DMD-40, Sullair Part Number 02250244-035. Vessel Diameter 5", Vessel Height 40", Vessel Thickness 1/3". Purge Exhaust Muffler 3/4". Inlet-Outlet Connection - Inches 1 1/2" NPT; Relief Valve Setting (psi) 200; Bed Velocity (fpm) 60; Sound Max dbA 85; Purge Source Dry Air; Purge Adjust CHECK VALVE; NEMA Cycle (Min) 5 min; Drying time (Min) 2.5 minutes; Regeneration Time (Min) 2 minutes; Repressurization Time (Min) 30 seconds; PERFORMANCE DATA: MAX Ambient Temp (Deg. F/ Deg. C) 122/50; MIN Ambient Temp (Deg. F/ Deg. C) 34 / 1.6 ; MAX Inlet Temp (Deg. F/ Deg. C) 122/50; Max Rated Air Flow at 100 Deg. F (38 Deg. C) ; Inlet, 100 psig (7 barg) and 100 Deg. F (38 Deg. C) Amb 40; Dryer Delta P 2; MIN Pressure (psi/bar) 58 / 4.0; MAX Pressure (psi/bar) 200 / 16; AVG Purge Rate (at -40 Deg. F) 15%; AVG Purge Rate (at -100 Deg. F) 20%; ELECTRICAL DATA: Standard Voltage 80-240V/ 50-60Hz; Full Load Amps 1; MIN. Circuit Ampacity 2; Input Power kW 0.075; Unit Average kW 0.06; DIMENSIONS &amp; WEIGHT DATA: Single Vessel Desiccant-Lbs 20.9; Ship Weight 164.5; Length-inches 16.1; Width-inches 17.7; Height-inches 49.2; UNIT Weight-lbs 143; Total Desiccant (lbs) 41.8.</p> <p>Serial# 4318MD00605</p>	250	3575 Morreim Dr, Belvidere, IL 61008