

MAJOR STAMPING MACHINERY AUCTION SALE

Complete Plant Closure of Dexter Stamping

Auction Closing Wed., Oct. 30th in Jackson, Mich.



Pre-Auction Offers to be
Considered on Major Assets

(248) 914-4226

www.levyrecovery.com



SELECT STAMPING PRESSES INCLUDED

Press Specifications:

Press		1	9*	20	27	32
Make		BLISS	BLISS	VERSION	MINSTER	MUELLER
Tonnage		300	150	800	600B	1000 Metric (1102 US TON)
Bed Size	L	72"	72"	108"	84"	4500mm (177")
	W	42"	36"	60"	48"	1200mm (47.25")
Ram Size	L	72"	72"	108"	84"	4500mm (177")
	W	36"	24"	60"	48"	1200mm (47.25")
Max Shut Height		20"	18"	30.0"	25.0"	700mm (27.562")
Ram Adj.		6"	4"	10"	6"	160mm (6.300")
Precision Shut Height		20.0"		24.25"	24.25"	700mm (27.562")
Feed Height (above Bolster)		9.5" ±1	10.5" ± 0.25	NA	12" ±1	500mm (19.687")
Window Size	W	27"	18"	40"	33"	900mm (35.437")
	H	23"	12"	20"	20"	500mm (19.687")
Stroke		6"	6"	16"	12"	450mm (17.71")
Strokes/Minute		0 – 70	30 – 90	18 – 20	0 – 60	5 – 45
Bolster Thickness		7"	6"	18"	7"	140mm (5.512")
Coil Box OD (Min)						
Coil Box OD (Max)		60"		20"	60"	
Capacity (lbs)		6,000	2500-4000	2500-4000	10,000	9070kg (19,997 LBS)
Max Coil (lbs)		6,000			10,000	13,000
Coil I.D.		20"		20"	20"	20"
Coil O.D. Max		48"			60"	72"
Coil O.D. Min		36"			36"	60"
Straightener Width		12" Max	N/A	18"	36" Max	1016mm (40")
Straightener Thickness	MIN	0.02	N/A	0.02	0.02	1.00mm
	MAX	0.1		0.1	0.240 @ 36"	6.35mm
Feeder Width		12" Max	16"	24"	30" Max	1016mm (40")
Feeder Thickness	MIN	0.02		0.02	0.02	1.00mm (.039")
	MAX	0.1	0.187	0.1	0.28"	6.35mm (.250")
Feeder Stroke		99"		99"	99"	99"